

### DESCRIPTION and USES

This product is designed to give one coat block-out hiding on interior wall and ceiling surfaces. Flash rust inhibition is provided over lightly rusted steel which allows this product to be applied over most interior structural steel surfaces without extensive surface preparation. Other features of this paint are low odor, non-flammability and water clean up. Under proper humidity and temperature conditions, the overspray from this paint will dry to a powder that will not damage floors or equipment. This product meets VOC requirements for use in LEED construction.

### SURFACE PREPARATION

Surfaces must be dry, free of dirt, grease and other contaminants. All loose and peeling paint should be removed. Moderately or heavily rusted surfaces must be primed with METL-CLAD 449 Metal Primer.

### APPLICATION

Apply with roller or airless spray. If dry overspray or flash rust resistance properties are important, do not apply at temperatures below 65°F, if relative humidities are above 70% or if the dew point is within 5° of the air temperature. As this product is applied, the relative humidity of the air will increase, slowing the dry time of this paint. A good flow of fresh air must be maintained to preserve the dry mist property of this paint.

### SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### COLORS

This product is available in white, black and light tone colors. Custom colors available by special order.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Finish:</b>	Semi-Gloss
<b>Vehicle Type:</b>	Vinyl Acrylic Latex
<b>Volume Solids:</b>	39%
<b>Coverage:</b>	200 – 300 SF/Gallon
<b>Dry Time:</b>	
<i>Touch:</i>	30 Minutes
<i>Recoat:</i>	2 Hours
<b>Primer:</b>	
	Self Prime over most surfaces.
<b>VOC:</b>	47 g/l
<b>Clean Up:</b>	Water

### PRODUCT CODE INFORMATION

41710	Dry Mist Latex S/G—White
41770	Dry Mist Latex S/G—Black

**RepcoLite Paints, Inc.**  
473 W. 17<sup>th</sup> St.  
Holland, MI 49423  
(616) 396-1275  
[www.repcolite.com](http://www.repcolite.com)