

DESCRIPTION and USES

This latex floor paint combines a durable, wear resistant finish and easy application with water clean up of painting tools. It can be used on concrete or wood floors, inside or outside. It is ideal for use on basement floors, patios and porches. It can also be used on concrete or bituminous tennis courts. DO NOT use this paint on garage floors. The quick dry feature of this paint allows floors to be open to light traffic in 2 to 3 hours, depending on drying conditions.

SURFACE PREPARATION

All surfaces to be painted must be free of dirt, dust, grease and wax. New concrete floor should cure for 30 days before painting. Remove soap scum from around laundry areas. Scrub floor with Trisodium Phosphate (TSP) solution. Rinse well with clear water. Very dusty or smooth concrete floors should be cleaned and etched with a 10% solution of Muriatic Acid in water. Dull old glossy paint with sandpaper to insure adhesion.

APPLICATION

Apply with a paint brush or roller. Two coats are recommended on all bare surfaces. Do not apply when surface or air temperature is below 50°F.

SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

A limited selection of RepcoLite *Color Folio* and *Color Studio* Colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Satin Sheen
Vehicle Type:	100% Acrylic Latex
Volume Solids:	31%
Coverage:	350 – 450 SF/Gallon
Dry Time:	
<i>Touch:</i>	30 – 45 Minutes
<i>Recoat:</i>	4 Hours
VOC:	Less than 400 g/l
Clean Up:	Water

PRODUCT CODE INFORMATION

46903	Aqua-Tred—33 Base
46906	Aqua-Tred—36 Base

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com